

Plotted by : KDOT#CADD.Support_ks.gov 8-JAN-2026 01:03
File : te590.dgn

DETAILED SPECIFICATIONS FOR FLAT SHEET SIGNS AND OVERLAY PANELS

All new flat sheet sign blanks shall be of the fabrication and thickness shown on the flat sheet blank detail sheets, unless other details are shown in the plans.

Flat sheet blanks shall be used for signs that are less than or equal to 7'-0" in length and/or less than or equal to 4'-0" in height, unless other details are shown in the plans. Flat sheet blanks shall also be used for signs that are 4'-0" in length and less than or equal to 8'-0" in height, unless other details are shown in the plans.

The design details for signs (color, letter height, and letter series) shall be as shown in the FHWA Standard Highway Signs and Markings book (Current version or any supplements), unless other details are shown in the plans.

All sign faces shall be covered with Type IV high intensity retroreflective sheeting, unless otherwise noted in the plans.

The sheeting used for the direct applied legend and borders shall be Type IV high intensity retroreflective sheeting, unless otherwise noted in the plans.

The school warning signs, the "SCHOOL" portion of the S5-1 sign, S4-3p plaque, and any supplemental plaques used with these warning signs shall have a fluorescent yellow-green background, unless otherwise noted in the plans.

The type of adhesive used for retroreflective sheeting or lettering film shall be heat activated or pressure sensitive.

DETAILED SPECIFICATIONS FOR REINFORCED PANEL SIGNS

All new reinforced sign panels shall be of the fabrication and thickness shown on the reinforced panel detail sheets. If extrusheet fabricated sign panels are used, they shall be of the length, width and in the position shown. If extrusheet fabricated panel dimensions are not shown, a line of legend should be placed entirely on one panel. If extruded fabricated sign panels are used, either 1'-0" or 6" panels shall be used. The 6" panels shall be used only at the top or bottom of signs.

Reinforced panels shall be used for signs that are greater than 7'-0" in length or greater than 4'-0" in height, unless other details are shown in the plans.

All sign faces shall be covered with Type IV high intensity retroreflective sheeting, unless otherwise noted in the plans.

The sheeting used for the direct applied legend and borders shall be Type IV high intensity retroreflective sheeting, unless otherwise noted in the plans.

The type of adhesive used for retroreflective sheeting or lettering film shall be heat activated or pressure sensitive.

Letters and numbers on reinforced panel signs are modified Series "E" unless otherwise shown.

Spacing table dimensions are in inches.

STATE	PROJECT NO.	YEAR	SHEET NO.	TOTAL SHEETS
KANSAS	0	0	0	0

03	09-16-25	Changed 2004 to current version	D.D.G.	N.T.J.
02	10-01-19	Changed notes	D.D.G.	E.W.N.
01	07-23-10	Changed Notes and Sheeting Type	D.D.G.	D.B.
NO.	DATE	REVISIONS	BY	APPD
KANSAS DEPARTMENT OF TRANSPORTATION				
DETAILS SPECIFICATIONS FOR REINFORCED SIGN PANELS AND FLAT SHEET SIGNS				
TE590			07-01-03	
FHWA APPROVAL		12-08-25	APPD.	Steven A. Buckley
DESIGNED	D.D.G.	DETAILED	K.D.S.	QUANTITIES
DESIGN CK.	S.A.B.	DETAIL CK.	D.D.G.	QUAN.CK.
		TRACED		
		TRACE CK.		